

Clausing Kalamazoo Large Capacity 14" x 40" Vertical Bandsaws

Features:

- 230/460/60/3 Electricals
- Magnetic Starter with 110V Control Circuit and Overload Protection
- 5 Hp TEFC Motor, with Brake (full stop from max. speed within 10 seconds)
- Dual Range Transmission
- 1" (25.4mm) Chevron type Blade Guides with Back-Up Roller
- 29" (737mm)W x 27" (686mm)L Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R)
- 29-1/2" (749mm)W x 27-.1/2" (699mm)L Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top (Hydraulic table only) Table Travel 13" (330mm)
- Auxiliary Table 19" (483mm)W x 26-3/4" (679mm)L
- Bonded Rubber Band Wheels
- 110V Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 1" (25.4mm) Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) Year Limited Warranty

Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder (Carbon stock only)
- Rip Fence
- Circle Cutting Attachment
- Miter Gauge
- Workholding Jaws
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts



Specifications:

Model	V4014F	V4014H
Throat	40" (1016mm)	40" (1016mm)
Work Height	14" (356mm)	14" (356mm)
Table Height	54" (1372mm)	54" (1372mm)
Drive Motor	5 Hp (3.75Kw)	5 Hp (3.75Kw)
Blade Length	260"-263" (6604-6680mm)	260"-263" (6604-6680mm)
Blade Width	1/8"-1 1/4" (3-25mm)	1/8"-1 1/4" (3-25mm)
Blade Speed (fpm)	50-5200	50-5200
Dimensions		
Length	72" (1829mm)	72" (1829mm)
Width	39" (991mm)	39" (991mm)
Height	113" (2870mm)	113" (2870mm)
Net Weight	2,976 lbs. (1350 kg)	3,395 lbs. (1540 kg)
Shipping Weight	3,395 lbs. (1540kg)	3,627 lbs. (1645 kg)

All specifications subject to change without notice or obligation.